

TECHNICAL DATA

BMV PRO EC 1.3

Phase, rated power [V]	1~ 230V
Power supply range [V]	200- 240
Frequency [Hz]	50-60Hz
Max power consumption [W]	27
Max current consumption [A]	0.27
Operating temperature range [°C]	-25°C<T<+55°C
Weight [kg]	3,65
Protection class IP/ insulation class	IP 54 cl. B

BMV PRO EC 1.9

Phase, rated power [V]	1~ 230V
Power supply range [V]	200- 240
Frequency [Hz]	50-60Hz
Max power consumption [W]	90
Max current consumption [A]	0,76
Operating temperature range [°C]	-25°C<T<+60°C*
Weight [kg]	3,5
Protection class IP/ insulation class	IP 54 cl. B

BMV PRO EC 2.2

Phase, rated power [V]	1~ 230V
Power supply range [V]	200- 240
Frequency [Hz]	50-60Hz
Max power consumption [W]	90
Max current consumption [A]	0,8
Operating temperature range [°C]	-25°C<T<+60°C *
Weight [kg]	4,16
Protection class IP/ insulation class	IP 54 cl. B

BMV PRO EC 2.5

Phase, rated power [V]	1~ 230V
Power supply range [V]	200- 240
Frequency [Hz]	50-60Hz
Max power consumption [W]	170
Max current consumption [A]	1,5
Operating temperature range [°C]	-25°C<T<+60°C *
Weight [kg]	5.0
Protection class IP/ insulation class	IP 54 cl. B