

TECHNICAL DATA

BMV PRO EC Vertical 1.3

| | |
|---------------------------------------|-------------------|
| Phase, rated power [V] | 1- 230V |
| Power supply range [V] | 200- 240 |
| Frequency [Hz] | 50-60Hz |
| Max power consumption [W] | 27 |
| Max current consumption [A] | 0,27 |
| Operating temperature range [oC] | -25°C < T < +55°C |
| Weight [kg] | 5 |
| Protection class IP/ insulation class | IP 54 cl. B |

BMV PRO EC Vertical 1.9

| | |
|---------------------------------------|-------------------|
| Phase, rated power [V] | 1-230V |
| Power supply range [V] | 200- 240 |
| Frequency [Hz] | 50-60Hz |
| Max power consumption [W] | 90 |
| Max current consumption [A] | 0,76 |
| Operating temperature range [oC] | -25°C < T < +55°C |
| Weight [kg] | 5 |
| Protection class IP/ insulation class | IP 54 cl. B |

BMV PRO EC Vertical 2.2

| | |
|---------------------------------------|-------------------|
| Phase, rated power [V] | 1-230V |
| Power supply range [V] | 200- 240 |
| Frequency [Hz] | 50-60Hz |
| Max power consumption [W] | 90 |
| Max current consumption [A] | 0,8 |
| Operating temperature range [oC] | -25°C < T < +55°C |
| Weight [kg] | 6 |
| Protection class IP/ insulation class | IP 54 cl. B |

BMV PRO EC Vertical 2.5

| | |
|---------------------------------------|-------------------|
| Phase, rated power [V] | 1-230V |
| Power supply range [V] | 200- 240 |
| Frequency [Hz] | 50-60Hz |
| Max power consumption [W] | 170 |
| Max current consumption [A] | 1,5 |
| Operating temperature range [oC] | -25°C < T < +55°C |
| Weight [kg] | 7 |
| Protection class IP/ insulation class | IP 54 cl. B |